

# ???????? ???? MBK17-BSR-2104 ?? MBK17-BSR-2114

?????:  
????????? ??: MBK17-BSR-2000



????????? ????  
????????? ????  
?????? ???? ???? MBK17-BSR-2104 & MBK17-BSR-2114 ??????  
?????? ????  
?????? ???? ???? LCD ??????  
?????? ????.

<b>????????????</b>	
OPERATION VOLTAGE	21-28V DC
BEACON	1 Power LED
TYPE OF APPLICATION	type B
ENVIRONMENT	
MOUNTING	Wall
COVERAGE (y)	6 m around the siren at an angle of 180°
MOUNTING HEIGHT (x)	2.4m max
COVERAGE VOLUME CODE	W-2.4-6
COVERAGE VOLUME	86.4m <sup>3</sup> (max)
FLASH RATE	1 Hz (Switchable to 0.5 Hz)
FLASH COLOUR	Red
DEGREES OF COVER PROTECTION	IP 65
PRODUCED IN ACCORDANCE WITH	EN 54-3: 2001 +?1:2002 +?2:2006, EN

	54-23: 2010
OPERATION TEMPERATURE RANGE	0 to 60 o C
RELATIVE HUMIDITY	Up to 95%
CONSTRUCTION MATERIAL	Bayblend FR3010, transparent polycarbonate
EXTERNAL DIMENSIONS	141 x 141 x 100 mm
TYPICAL WEIGHT	240gr.
GUARANTEE	2 years