

CODE: MBK04-010AF-P1C

ERP: 0135100

Fire Extinguisher 1Lt Foam Portable

Fire Extinguisher 1Lt Foam (1,5%) with one seam vessel with INTERNAL PLASTIC LAYER and Pressure Gauge
Safety Release Valve. METALLIC BRACKET INCLUDED



CHARACTERISTICS

Capacity	1Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	1,09 lt
Cylinder Height	270±2 mm
Cylinder Diameter	85±1 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	2,2 kg
Approx. Dimensions	370x100 mm
Paint Finish	RAL 3000
Packaging Details	6 pcs.

CE

Issue Date: 13/10/2021

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiakfire.com