

CODE: MBK06-100CA-P1A

ERP: 0129000

Trolley Fire Extinguisher 10Kg CO2 Trolley

10Kg CO2 Trolley Fire Extinguisher with 16Lt Cylinder with 5m Discharge Hose.

HIGH-PRESSURE EPDM Discharge Hose of WP 155bar with Wooden Handle and Flow Control Valve, according to EN853 requirements, HEAVY Duty Carriage and wheels, Valve Protection HANDLE



CHARACTERISTICS

Capacity	10Kg
Extinguishing Agent	CO2
Operating Temperature	-20 to +60 °C
Max Allowable Pressure	174 bar
Test Pressure	300 bar
Volume of Equipment	16 lt
Cylinder Height	685±6,85 mm
Cylinder Diameter	200±2 mm
Cylinder Neck Thread	25E
Valve Material	DC01 (St12)
Cylinder Material	HPb59-1 (Nickel Plated)
Safety Valve	250-275 bar
Approx. gross Weight	63,8 kg
Approx. Dimensions	1100x400 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

EN1866



CE

2010/35/EU (IT)

EN1964

Issue Date: 12/03/2020

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiak.com