

CODE: MBK18-500AF-W1B

ERP: 0135494

## Trolley Fire Extinguisher 50Lt Foam - NF Trolley

Trolley Fire Extinguisher, 50Lt , with 5m Discharge Hose. Vessel with Internal Plastic layer. Valve with Gauge Safety Release Mechanism. 3rd Wheel added on the Front Side of the Fire Extinguisher Carriage for Easier Usage- Handling.

Soft Material is used in the retaining wreaths of the vessel to avoid injuries and oxidation



### CHARACTERISTICS

Capacity	50Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	28 bar
Volume of Equipment	56,2±1 lt
Cylinder Height	900±10 mm
Cylinder Diameter	305±3 mm
Cylinder Neck Thread	G2"
Cylinder Material	HP295
Valve Material	HPb59-1 (Nikel Plated)
Safety Valve	22-28 bar
Approx. gross Weight	94,8 kg
Approx. Dimensions	1300x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



BENOR

Issue Date: 11/03/2020

Information may change

**FACTORY:** AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

**CENTRAL EXHIBITION:** 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

**ATHENS DISTRIBUTION CENTER:** SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

**N.GREECE DISTRIB. CENTER:** 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

**CENT. & EAST CRETE DISTRIB. CENTER:** P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

[www.mobiak.com](http://www.mobiak.com)