

CODE: MBK14-250PA-WLD

ERP: 0135339

Trolley Fire Extinguisher 25Kg Dry Powder Welded Trolley

25Kg Dry Powder Welded Trolley Fire Extinguisher with 5m Discharge Hose and High Strength Wheels. Pressure Gauge Safety Release Valve.



CHARACTERISTICS

Capacity	25 Kg
Extinguishing Agent	ABC40%
Operating Temperature	-30 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	28 bar
Volume of Equipment	31 lt
Cylinder Height	520±5 mm
Cylinder Diameter	305±3 mm
Cylinder Neck Thread	G2
Valve Material	HPb59-1 (Nickel Plated)
Cylinder Material	HP295
Safety Valve	22-28 bar
Approx. gross Weight	60 kg
Approx. Dimensions	950x550 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.

CE

EN1866

Issue Date: 28/07/2021

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P¹ str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiak.com