

CODE: MBK07-060AF-P1E

ERP: 0501025

Fire Extinguisher 6Lt Foam Portable

Fire Extinguisher 6Lt Foam 1,5%, with one seam vessel with Internal Plastic Layer and Pressure Gauge
Safety Release Valve.

Metallic bracket included



CHARACTERISTICS

Capacity	6Lt
Extinguishing Agent	BSX233 1,5%
Operating Temperature	+5 to +60 °C
Max Allowable Pressure	18 bar
Test Pressure	27 bar
Volume of Equipment	7,9 lt
Cylinder Height	470±5 mm
Cylinder Diameter	160±1,5 mm
Cylinder Neck Thread	M30x1,5
Valve Material	HPb59-1 (Nikel Plated)
Cylinder Material	DC01 (St12)
Safety Valve	19-26 bar
Approx. gross Weight	10,5 kg
Approx. Dimensions	630x200 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



Issue Date: 13/10/2021

Information may change

FACTORY: AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

CENTRAL EXHIBITION: 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

ATHENS DISTRIBUTION CENTER: SXINEZA- ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

N.GREECE DISTRIB. CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

CENT. & EAST CRETE DISTRIB. CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

www.mobiakfire.com